## NSN 5305-00-338-3303

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-338-3303 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.554 inches and 0.604 inches **Fastener Length:** Between 1.002 inches and 1.032 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.717 inches and 0.760 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Titanium alloy **Material Specification:** Nas 621 comp 6al-4v assn standard single material response or ams 4928 assn standard single material response

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas666 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-338-3303

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0