
Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-338-6085

Т	hread Class:
3	a
T	Thread Direction:
F	Right-hand
T	hread Length:
E	Between 0.528 inches and 0.640 inches
F	astener Length:
E	Between 0.610 inches and 0.640 inches
ŀ	lead Style:
F	Tat chamfer
ŀ	lead Diameter:
E	Between 0.429 inches and 0.438 inches
ŀ	lead Height:
E	Between 0.306 inches and 0.313 inches
H	lole Diameter:
C	0.060 inches
l	nternal Drive Style:
ŀ	lexagon
T	Thread Diameter:
С	0.312 inches
V	Vidth Across Flats:
E	Between 0.218 inches and 0.221 inches
ŀ	Iole Quantity:
6	;
ŀ	lole Type:
D	Drilled
T	hready Qty Per Inch (tpi):
2	4
Ν	/in. Tensile Strength (psi):
1	50000 pounds per square inch
ŀ	lole Configuration Style:
F	Round internal hexagon
Ν	Naterial:
Т	itanium alloy
Ν	Naterial Specification:
A	Ams 4928 assn standard single material response
T	hread Series Designator:
ι	Jnjf
S	Shelf Life:
٩	N/a
ι	Jnit Of Measure:

NSN 5305-00-338-6085

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

