NSN 5305-00-339-8097

Assembled Washer Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-339-8097



| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.156 inches |
| Fastener Length: |
| 0.187 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.094 inches |
| Width Between Flats: |
| 0.250 inches |
| Washer Quantity: |
| 1 |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Primary Washer Outside Diameter: |
| 0.327 inches |
| Primary Washer Style: |
| |
| Spring tension |
| Spring tension Primary Washer Material Thickness: |
| |
| Primary Washer Material Thickness: |
| Primary Washer Material Thickness: 0.028 inches |
| Primary Washer Material Thickness: 0.028 inches Material: |
| Primary Washer Material Thickness: 0.028 inches Material: Steel |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide Thread Series Designator: |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide Thread Series Designator: Unf |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: |
| Primary Washer Material Thickness: 0.028 inches Material: Steel Surface Treatment: Oxide Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: |