NSN 5305-00-340-4445

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-340-4445 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.321 inches and 1.433 inches **Fastener Length:** Between 1.438 inches and 1.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.195 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Stainless steel **Screw Material Specification:** Qq-s-763, 300 series federal specification single material response or 66, 300 series federal standard single material response or comp 16-18 or 18-8 assn standard single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization:

NSN 5305-00-340-4445

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.