## NSN 5305-00-340-6000

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-340-6000 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.813 inches and 0.875 inches **Fastener Length:** 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.142 inches and 0.147 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.312 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 **Material Specification:** Qq-s-763 federal specification all material responses or 66 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

**Unit Of Measure:** 

Shelf Life:

Unf

N/a

## NSN 5305-00-340-6000

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0