3a

40

N/a

---

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-341-7397



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.186 inches and 0.267 inches Fastener Length: Between 0.281 inches and 0.312 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.177 inches and 0.225 inches Locking Feature: Patch threads or pellet threads or strip threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1189 professional/industrial association standard Shelf Life: Unit Of Measure:

## NSN 5305-00-341-7397

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

