NSN 5305-00-342-7141

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-342-7141 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.322 inches **Fastener Length:** Between 1.130 inches and 1.150 inches **Head Style:** Fillister **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.140 inches and 0.160 inches **Second Diameter From Head:** Between 0.117 inches and 0.121 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.110 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.718 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 1010 or steel comp 1011 **Material Specification:** Qq-s-633 federal specification all material responses **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3, dyed black federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-342-7141

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0