## NSN 5305-00-345-2377

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-345-2377 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.152 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.126 inches and 0.176 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Iron alloy 660 **Locking Feature Material:** Plastic polyethylene **Screw Material Specification:** Ams 5737 assn standard single material response **Locking Feature Material Specification:** Ams 3612 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc

N/a

Shelf Life:

## NSN 5305-00-345-2377

Machine Screw - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A500d0