NSN 5305-00-347-7847

Close Tolerance Screw - Page 1 of 1





View Online at https://aerobasegroup.com/nsn/5305-00-347-7847

| Thread Class: |
|--|
| |
| 3a Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| Between 0.251 inches and 0.301 inches |
| Fastener Length: |
| Between 0.699 inches and 0.729 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| Grip Diameter: |
| Between 0.1881 inches and 0.1887 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams4928 assn standard single material response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |