NSN 5305-00-347-8355

Shoulder Screw - Page 1 of 2

3a

28





Thread Class: Thread Direction: Right-hand Thread Length: Between 0.443 inches and 0.510 inches Fastener Length: Between 1.078 inches and 1.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.502 inches and 0.507 inches **Head Height:** Between 0.065 inches and 0.067 inches **Shoulder Diameter:** 0.264 inches first shoulder and 0.265 inches first shoulder Shoulder Length: 0.548 inches first shoulder and 0.570 inches first shoulder **Internal Drive Style:** High-torque Thread Diameter: 0.250 inches Thready Qty Per Inch (tpi): **Countersink Angle:** 100.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Furnished with one o-ring Material: Steel **Material Specification:** 3-52 fscm 76301 mfr ref single material response Surface Treatment: Cadmium **Surface Treatment Specification:** 3-52 fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

NSN 5305-00-347-8355

Shoulder Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

