## NSN 5305-00-351-3938

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-351-3938 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.323 inches and 0.353 inches **Fastener Length:** Between 0.528 inches and 0.548 inches **Head Style:** Hexagon **Head Height:** Between 0.040 inches and 0.050 inches Width Between Flats: Between 0.184 inches and 0.188 inches **Shoulder Diameter:** 0.1243 inches first shoulder and 0.1247 inches first shoulder **Shoulder Length:** 0.195 inches first shoulder and 0.205 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-std-171 finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig: A003b0

## NSN 5305-00-351-3938

Shoulder Screw - Page 2 of 2



Mil-std (military Standard):

Mil-std-171 spec.