## NSN 5305-00-353-0969

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-353-0969 **Thread Class:** 2a **Thread Direction:** Right-hand **Thread Length:** 0.969 inches **Fastener Length:** Between 1.174 inches and 1.184 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.292 inches and 0.302 inches **Head Height:** 0.109 inches **First Diameter From Head:** Between 0.175 inches and 0.185 inches **Second Diameter From Head:** Between 0.292 inches and 0.302 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.081 inches and 0.091 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.143 inches and 0.153 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity: Special Features:** W/header point Material: Steel comp 1212 or steel comp 1213 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 **Material Specification:** Qq-s637 federal specification 1st material response or qq-s-637 federal specification 2nd material response **Surface Treatment:** 

Unf

Cadmium and chromate

**Thread Series Designator:** 

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification all treatment responses

## NSN 5305-00-353-0969

Externally Relieved Body Screw - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0