## NSN 5305-00-356-4236

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-356-4236 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** 0.984 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.484 inches and 0.516 inches **Head Height:** Between 0.297 inches and 0.328 inches **First Diameter From Head:** Between 0.141 inches and 0.172 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.609 inches and 0.641 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Head knurled Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-356-4236

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0