NSN 5305-00-356-4309

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-356-4309 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.609 inches and 0.641 inches **Fastener Length:** Between 1.859 inches and 1.891 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.382 inches and 0.408 inches **Head Height:** Between 0.125 inches and 0.157 inches **First Diameter From Head:** Between 0.123 inches and 0.155 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.218 inches and 1.282 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 90 degrees angle Material: Steel comp 1212 **Material Specification:** Saejggaisi assn standard all material responses or 66 federal standard all material responses **Surface Treatment:** Dichromate zinc **Surface Treatment Specification:** Qq-z-325, type 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-356-4309

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0