## NSN 5305-00-357-9827

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-357-9827 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.322 inches **Fastener Length:** Between 0.745 inches and 0.755 inches **Head Style:** Pan **Head Diameter:** Between 0.317 inches and 0.327 inches **Head Height:** Between 0.110 inches and 0.120 inches **First Diameter From Head:** Between 0.120 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.433 inches and 0.443 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 or steel comp 1011 or steel comp 1013 **Material Specification:** Aisi assn standard all material responses **Surface Treatment:** Cadmium or chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-357-9827

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0