NSN 5305-00-357-9829

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-357-9829 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.220 inches and 0.270 inches **Fastener Length:** Between 0.620 inches and 0.630 inches **Head Style:** Pan **Head Diameter:** Between 0.368 inches and 0.378 inches **Head Height:** Between 0.128 inches and 0.138 inches **First Diameter From Head:** Between 0.133 inches and 0.143 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.360 inches and 0.400 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 or steel comp 1011 or steel comp 1013 **Material Specification:** Aisi assn standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-357-9829

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0