NSN 5305-00-357-9830

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-357-9830 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.320 inches and 0.400 inches **Fastener Length:** Between 0.840 inches and 0.880 inches **Head Style:** Hexagon **Head Height:** Between 0.120 inches and 0.130 inches Width Between Flats: 0.250 inches **First Diameter From Head:** Between 0.118 inches and 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.480 inches and 0.520 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1018 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-357-9830

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0