

View Online at <https://aerobasegroup.com/nsn/5305-00-363-3976>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.525 inches and 0.625 inches

Fastener Length:

0.625 inches

Head Style:

Hexagon

Head Height:

Between 0.172 inches and 0.190 inches

Width Between Flats:

Between 0.367 inches and 0.375 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

74000 pounds per square inch

Hardness Rating:

80.0 rockwell b and 100.0 rockwell b

Minimum Yield Strength:

57000 pounds per square inch

Primary Washer Outside Diameter:

Between 0.494 inches and 0.510 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.023 inches and 0.028 inches

Material:

Steel

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Ams 2400 assn standard 1st treatment response or ams 2402 assn standard 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0