## NSN 5305-00-363-3976

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-363-3976 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.525 inches and 0.625 inches **Fastener Length:** 0.625 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.367 inches and 0.375 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b Minimum Yield Strength: 57000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.494 inches and 0.510 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches Material: Steel **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Ams 2400 assn standard 1st treatment response or ams 2402 assn standard 2nd treatment response

Unc

**Thread Series Designator:** 

## NSN 5305-00-363-3976

Assembled Washer Screw - Page 2 of 2



She	lf I	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0