NSN 5305-00-363-3984

Between 0.250 inches and 0.312 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

0.312 inches **Head Style:**Hexagon

2a

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-363-3984

Head Height:
Between 0.172 inches and 0.190 inches
Width Between Flats:
Between 0.367 inches and 0.375 inches
Washer Quantity:
1
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
74000 pounds per square inch
Hardness Rating:
80.0 rockwell b and 100.0 rockwell b
Minimum Yield Strength:
57000 pounds per square inch
Primary Washer Outside Diameter:
Between 0.494 inches and 0.510 inches
Primary Washer Style:
Flat external teeth
Primary Washer Material Thickness:
Between 0.023 inches and 0.028 inches
Material:
Steel
Material Specification:
Sae grade 2 assn standard single material response
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Ams2400-1 assn standard 1st treatment response or ams2402-1 assn standard 2nd treatment response

NSN 5305-00-363-3984

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0