2a

1

32

Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-363-3990



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.188 inches and 0.250 inches Fastener Length: 0.250 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.367 inches and 0.375 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 74000 pounds per square inch Hardness Rating: 80.0 rockwell b and 100.0 rockwell b **Minimum Yield Strength:** 57000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.395 inches and 0.410 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.020 inches and 0.025 inches Material: Steel **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Ams 2400 assn standard 1st treatment response or ams 2402 assn standard 2nd treatment response **Thread Series Designator:**

Unc

## NSN 5305-00-363-3990

Assembled Washer Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

