

View Online at <https://aerobasegroup.com/nsn/5305-00-364-9394>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.881 inches and 0.931 inches

**Fastener Length:**

Between 2.203 inches and 2.233 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.071 inches and 1.140 inches

**Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 1.302 inches and 1.322 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Navy special project

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas589 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.