## NSN 5305-00-364-9423

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-364-9423 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.213 inches and 0.223 inches **Fastener Length:** Between 0.468 inches and 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.097 inches and 0.101 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.245 inches and 0.287 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8630 or steel comp 4037 **Material Specification:** Ams 6300 assn standard all material responses or mil-s-6050 military specification all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc

N/a

Shelf Life:

## NSN 5305-00-364-9423

Externally Relieved Body Screw - Page 2 of 2



--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.