

View Online at <https://aerobasegroup.com/nsn/5305-00-365-2771>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.200 inches

**Fastener Length:**

2.100 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.257 inches and 0.279 inches

**First Diameter From Head:**

Between 0.128 inches and 0.138 inches

**Second Diameter From Head:**

Between 0.090 inches and 0.100 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

1.200 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.900 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Stainless steel

**Material Specification:**

Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6050 spec.