Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-365-2974

Thread Cla	ISS:
2a	
Thread Dir	ection:
Right-hand	
Thread Lei	ngth:
0.720 inche	25
Fastener L	ength:
0.870 inche	95
Head Style	
Pan no. 2	
Head Diam	neter:
0.312 inche	25
Head Heig	ht:
0.155 inche	25
First Diam	eter From Head:
Between 0.	140 inches and 0.150 inches
Distance F	rom Largest Bearing Surface Of Head To End Of First Diameter:
0.150 inche	25
Internal Dr	ive Style:
Slot	
Thread Dia	imeter:
0.190 inche	25
Thready Q	ty Per Inch (tpi):
32	
Externally	Relieved Body Diameter Quantity:
1	
Material:	
Steel comp	303
Material Sp	pecification:
Mil-s-7720	military specification single material response
Surface Tr	eatment:
Passivate	
Surface Tr	eatment Specification:
Mil-f-14072	, finish e300 military specification single treatment response
Thread Se	ries Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-s-7720 spec.