## NSN 5305-00-366-9211

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-366-9211 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 1.359 inches and 1.391 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.433 inches and 0.443 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.990 inches and 1.010 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303se **Material Specification:** Mil-w-52263c military specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-366-9211

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-w-52263c spec.