## NSN 5305-00-367-8735

Setscrew - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5305-00-367-8735



## 3a **Thread Direction: Right-hand Thread Length:** Between 0.148 inches and 0.220 inches Fastener Length: Between 0.428 inches and 0.448 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Point Length:** Between 0.208 inches and 0.238 inches **Point Diameter:** Between 0.135 inches and 0.145 inches **Point Style:** Flat **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Point Chamfer Angle:** Between 24.0 degrees and 35.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5305-00-367-8735

Setscrew - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

