NSN 5305-00-367-8768



Setscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-367-8768 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.335 inches and 0.345 inches **Fastener Length:** Between 0.740 inches and 0.760 inches **Head Height:** Between 0.279 inches and 0.299 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.370 inches and 0.375 inches **Extended Washer Thickness:** Between 0.030 inches and 0.045 inches

Point Length:

Between 0.395 inches and 0.425 inches

Point Diameter:

Between 0.143 inches and 0.145 inches

Point Style:

Flat

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

130000 pounds per square inch

Minimum Yield Strength:

120000 pounds per square inch

Point Chamfer Angle:

90.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5305-00-367-8768

Setscrew - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0