## NSN 5305-00-369-2340

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-369-2340 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.297 inches and 0.327 inches **Fastener Length:** Between 0.668 inches and 0.708 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.485 inches and 0.515 inches **Head Height:** Between 0.105 inches and 0.135 inches **First Diameter From Head:** Between 0.244 inches and 0.249 inches **Second Diameter From Head:** Between 0.139 inches and 0.163 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.110 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.301 inches and 0.371 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

N/a

Unf

Shelf Life:

**Thread Series Designator:** 

## NSN 5305-00-369-2340

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0