## NSN 5305-00-369-2447

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-369-2447 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.120 inches **Fastener Length:** 0.260 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.207 inches and 0.225 inches First Diameter From Head: 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.092 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Pellet type locking feature in thread Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-369-2447

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0