
Socket Head Cap Screw - Page 1 of 2





| Thread Class:   |  |
|---|--|
| 3a  |  |
| Thread Direction:                                       |  |
| Right-hand  |  |
| Thread Length:  |  |
| Between 0.104 inches and 0.172 inches                   |  |
| Fastener Length:  |  |
| Between 0.140 inches and 0.172 inches                   |  |
| Head Style:   |  |
| Flat chamfer  |  |
| Head Diameter:  |  |
| Between 0.134 inches and 0.140 inches                   |  |
| Head Height:  |  |
| Between 0.083 inches and 0.086 inches                   |  |
| Hole Diameter:  |  |
| 0.023 inches  |  |
| Internal Drive Style:                                   |  |
| Hexagon   |  |
| Thread Diameter:  |  |
| 0.086 inches  |  |
| Width Across Flats:                                     |  |
| 0.078 inches  |  |
| Hole Quantity:  |  |
| 1   |  |
| Hole Type:  |  |
| Drilled   |  |
| Thready Qty Per Inch (tpi):                             |  |
| 56  |  |
| Hardness Rating:  |  |
| 34.0 rockwell c   |  |
| Hole Configuration Style:                               |  |
| Round   |  |
| Material:   |  |
| Steel comp 416  |  |
| Material Specification:                                 |  |
| Astm a582 cond a assn standard single material response |  |
| Thread Series Designator:                               |  |
| Unc   |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Measure:  |  |
| -   |  |

## NSN 5305-00-373-0127

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

