NSN 5305-00-379-4600

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-379-4600

View Online at https://aerobasegroup.com/nsn/5305-00-379-4600
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.291 inches and 0.341 inches
Fastener Length:
Between 1.363 inches and 1.393 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.506 inches
Shoulder Diameter:
0.2641 inches first shoulder and 0.2651 inches first shoulder
Shoulder Length:
1.052 inches first shoulder and 1.072 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
36.0 rockwell c and 40.0 rockwell c Countersink Angle:
Countersink Angle:
Countersink Angle: Between 99.0 degrees and 101.0 degrees
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Cadmium
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Cadmium Surface Treatment Specification:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unjf
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas1244 professional/industrial association standard
Countersink Angle: Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 303 Surface Treatment: Cadmium Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unjf Specification Data:

N/a

NSN 5305-00-379-4600

Shoulder Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0