## NSN 5305-00-379-6530

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-379-6530

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.484 inches and 0.516 inches
Fastener Length:
1.344 inches
Head Style:
Flat chamfer
Head Diameter:
0.625 inches
Head Height:
0.125 inches
Shoulder Diameter:
0.4365 inches first shoulder and 0.4370 inches first shoulder
Shoulder Length:
0.316 inches first shoulder and 0.318 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.321 inches
Features Provided:
Casehardened
Thready Qty Per Inch (tpi):
24
Shoulder Shape:
Round first shoulder
Special Features:
Surface x casehardended to rc55 min rc60 max
Material:
Steel
Material Specification:
Fed standard 66, comp 4615 federal standard single material response
Surface Treatment:
Phosphate
Surface Treatment Specification:
Mil-c-16232, type 1 military specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

## NSN 5305-00-379-6530

Shoulder Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-16232 spec.