NSN 5305-00-382-4942

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-382-4942 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.484 inches and 0.516 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.484 inches and 0.516 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** 45 degree header point on thread end Material: Steel comp 303 **Material Specification:** Aisi assn standard 1st material response or astm assn standard 2nd material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-382-4942

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0