## NSN 5305-00-388-6020

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-388-6020 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.170 inches and 0.180 inches **Fastener Length:** 0.366 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.440 inches and 0.460 inches **Head Height:** Between 0.094 inches and 0.099 inches **Shoulder Diameter:** 0.310 inches first shoulder and 0.312 inches first shoulder **Shoulder Length:** 0.151 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Fed standard 66 federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-p-16232, type m, class 2 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-00-388-6020

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-p-16232 spec.