## NSN 5305-00-390-0685

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-390-0685 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 1.261 inches and 1.291 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.325 inches and 0.387 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 63.0 microinches threads **Product Name:** Navy special project **Material Specification:** Nas 621, 6al-4v assn standard 1st material response or ams 4928 assn standard 2nd material response **Thread Series Designator:** Unf **Specification Data:** 26512-gb510f manufacturers standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-390-0685

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0