

View Online at <https://aerobasegroup.com/nsn/5305-00-390-0685>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.363 inches

**Fastener Length:**

Between 1.261 inches and 1.291 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.325 inches and 0.387 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.928 inches and 0.948 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

63.0 microinches threads

**Product Name:**

Navy special project

**Material Specification:**

Nas 621, 6al-4v assn standard 1st material response or ams 4928 assn standard 2nd material response

**Thread Series Designator:**

Unf

**Specification Data:**

26512-gb510f manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0