NSN 5305-00-393-4040

Thread Class:

Passivate

Thread Direction:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-393-4040

Right-hand
Thread Length:
Between 0.428 inches and 0.520 inches
Fastener Length:
Between 0.490 inches and 0.520 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.221 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Hole Diameter:
0.037 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.093 inches and 0.095 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel
Material Specification:
66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66
federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material
response
Surface Treatment:

NSN 5305-00-393-4040

Socket Head Cap Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0