## NSN 5305-00-395-4983



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-395-4983 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.824 inches and 0.928 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.348 inches and 0.385 inches **Locking Feature:** Pellet or strip or patch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel **Screw Material Specification:** Qq-s-637 federal specification single material response or 66 federal standard single material response or astm a108 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 3 type and 3c style Shelf Life:

Demilitarization: No

**Unit Of Measure:** 

N/a

## NSN 5305-00-395-4983

Machine Screw - Page 2 of 2



Fiig:

A500d0