

View Online at <https://aerobasegroup.com/nsn/5305-00-395-5760>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.245 inches and 0.312 inches

Fastener Length:

Between 0.281 inches and 0.312 inches

Head Style:

Fillister

Head Diameter:

Between 0.145 inches and 0.161 inches

Head Height:

Between 0.061 inches and 0.070 inches

Internal Drive Style:

Slot

Thread Diameter:

0.099 inches

Thready Qty Per Inch (tpi):

56

Screw Material:

Copper alloy 268 or copper alloy 260 or copper alloy 240 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 342 or copper alloy 464 or copper alloy 270 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 210 or copper alloy 220 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-495 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-495 spec.