NSN 5305-00-395-5850



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-00-395-5850 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.782 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.257 inches and 0.263 inches **Head Height:** Between 0.074 inches and 0.080 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Screw Material:** Copper alloy 268 or copper alloy 260 or copper alloy 240 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 342 or copper alloy 353 or copper alloy 270 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 210 or copper alloy 220 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-f-495 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-std (military Standard):

Mil-f-495 spec.

A500d0