NSN 5305-00-395-6018

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-395-6018 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.307 inches and 0.317 inches **Fastener Length:** 1.250 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.495 inches and 0.505 inches **Head Height:** Between 0.547 inches and 0.577 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.740 inches and 0.760 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Patch type element on threads Material: Steel comp 302 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-395-6018

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0