NSN 5305-00-395-8674

Shoulder Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-395-8674

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.163 inches and 0.213 inches Fastener Length: Between 0.970 inches and 0.990 inches Head Height: Between 0.970 inches and 0.990 inches Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi):
Thread Direction:Right-handThread Length:Between 0.163 inches and 0.213 inchesFastener Length:Between 0.970 inches and 0.990 inchesHead Height:Between 0.248 inches and 0.268 inchesWidth Between Flats:0.250 inchesExtended Washer Diameter:Between 0.365 inches and 0.385 inchesExtended Washer Thickness:0.040 inchesShoulder Diameter:0.257 inches and 0.213 inches first shoulderShoulder Diameter:0.405 inches and 0.715 inches first shoulderShoulder Length:0.695 inches and 0.715 inches first shoulderInternal Drive Style:W/o internal driveThread Diameter:0.164 inches
Right-handThread Length:Between 0.163 inches and 0.213 inchesFastener Length:Between 0.970 inches and 0.990 inchesHead Height:Between 0.248 inches and 0.268 inchesWidth Between Flats:0.250 inchesExtended Washer Diameter:Between 0.365 inches and 0.385 inchesExtended Washer Thickness:0.040 inchesShoulder Diameter:0.207 inches and 0.213 inches first shoulderShoulder Length:0.695 inches and 0.715 inches first shoulderInternal Drive Style:W/o internal driveThread Diameter:0.164 inches
Thread Length:Between 0.163 inches and 0.213 inchesFastener Length:Between 0.970 inches and 0.990 inchesHead Height:Between 0.248 inches and 0.268 inchesWidth Between Flats:0.250 inchesExtended Washer Diameter:Between 0.365 inches and 0.385 inchesExtended Washer Thickness:0.040 inchesShoulder Diameter:0.207 inches and 0.213 inches first shoulderShoulder Length:0.695 inches and 0.715 inches first shoulderInternal Drive Style:W/o internal driveThread Diameter:0.164 inches
Between 0.163 inches and 0.213 inches Fastener Length: Between 0.970 inches and 0.990 inches Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive D.164 inches
Fastener Length:Between 0.970 inches and 0.990 inchesHead Height:Between 0.248 inches and 0.268 inchesWidth Between Flats:0.250 inchesExtended Washer Diameter:Between 0.365 inches and 0.385 inchesExtended Washer Thickness:0.040 inchesShoulder Diameter:0.207 inches and 0.213 inches first shoulderShoulder Length:0.695 inches and 0.715 inches first shoulderInternal Drive Style:W/o internal driveThread Diameter:0.164 inches
Between 0.970 inches and 0.990 inches Head Height: Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
Head Height:Between 0.248 inches and 0.268 inchesWidth Between Flats:0.250 inchesExtended Washer Diameter:Between 0.365 inches and 0.385 inchesExtended Washer Thickness:0.040 inchesShoulder Diameter:0.207 inches and 0.213 inches first shoulderShoulder Length:0.695 inches and 0.715 inches first shoulderInternal Drive Style:W/o internal driveD.164 inches
Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
 Width Between Flats: 0.250 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
0.250 inches Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
Extended Washer Diameter: Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
Between 0.365 inches and 0.385 inches Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
Extended Washer Thickness: 0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
0.040 inches Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
Shoulder Diameter: 0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
0.207 inches and 0.213 inches first shoulder Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
Shoulder Length: 0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
0.695 inches and 0.715 inches first shoulder Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
Internal Drive Style: W/o internal drive Thread Diameter: 0.164 inches
W/o internal drive Thread Diameter: 0.164 inches
Thread Diameter: 0.164 inches
0.164 inches
Thready Qty Per Inch (tpi):
32
Shoulder Shape:
Round first shoulder
Special Features:
Cage code 77445 is a oem and makes the item
Material:
Titanium alloy
Material Specification:
Ams4967 assn standard single material response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-395-8674

Shoulder Screw - Page 2 of 2

Fiig: A003b0

