

View Online at <https://aerobasegroup.com/nsn/5305-00-399-1049>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.039 inches and 0.145 inches

**Fastener Length:**

Between 0.156 inches and 0.188 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.257 inches and 0.279 inches

**Head Height:**

Between 0.043 inches and 0.055 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 202 or steel comp 302 or steel comp 304 or steel comp 303se or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp t15 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 429 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 446

**Screw Material Specification:**

Qq-s-763 federal specification single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Mil-f-14072 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**