

Socket Head Cap Screw - Page 1 of 2





| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.413 inches and 0.515 inches |
| Fastener Length: |
| Between 0.485 inches and 0.515 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.367 inches and 0.375 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Hole Diameter: |
| 0.060 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| Between 0.187 inches and 0.190 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 150000 pounds per square inch |
| Hole Configuration Style: |
| Round internal hexagon |
| Material: |
| Titanium alloy |
| Material Specification: |
| Ams 4928 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5305-00-399-1320

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

