## NSN 5305-00-399-7868

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-399-7868 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.378 inches **Head Style:** Flat chamfer **Head Diameter:** 0.312 inches **Head Height:** 0.094 inches **Shoulder Diameter:** 0.1855 inches first shoulder and 0.1870 inches first shoulder **Shoulder Length:** 0.065 inches first shoulder and 0.067 inches first shoulder **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder **Special Features:** Thd relief groove 0.062 in. Wide Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** 

Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-00-399-7868

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.