## NSN 5305-00-400-5527

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-400-5527 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 0.912 inches and 0.954 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.557 inches and 0.567 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.521 inches and 0.595 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point, 77 degrees min 87 degrees maximum angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-400-5527

Externally Relieved Body Screw - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0