## NSN 5305-00-401-4461

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-401-4461 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.267 inches and 0.423 inches **Fastener Length:** Between 0.409 inches and 0.469 inches **Head Style:** Round extended washer **Head Diameter:** 0.312 inches **Head Height:** Between 0.082 inches and 0.092 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.023 inches and 0.028 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Material: Steel comp 8630 or steel comp 4037 **Material Specification:** Mil-s-6050 military specification 1st material response or mil-s-8695 military specification 2nd material response **Surface Treatment:** Cadmium and zinc **Surface Treatment Specification:** An-p-61 military standard single treatment response and qq-z-325 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-401-4461

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.