NSN 5305-00-401-4736

Machine Screw - Page 1 of 2

Thread Class:

N/a



View Online at https://aerobasegroup.com/nsn/5305-00-401-4736

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.544 inches and 0.625 inches
Fastener Length:
Between 0.594 inches and 0.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.178 inches and 0.183 inches
Head Height:
Between 0.059 inches and 0.069 inches
Hole Diameter:
0.038 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.112 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material:
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification:
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment:
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment: Passivate
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification:
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Head Hole Configuration Style:
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Head Hole Configuration Style: Round
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator:
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Head Hole Configuration Style: Round Thread Series Designator: Unjc

NSN 5305-00-401-4736

Machine Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A500d0