NSN 5305-00-401-5152

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-401-5152 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.591 inches and 0.766 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.553 inches and 0.562 inches **Head Height:** Between 0.430 inches and 0.438 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.438 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate or zinc and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 3 federal specification 1st treatment response or qq-z-325 type 2, cl 2 federal specification 2nd treatment response **Thread Series Designator:** Unc **Specification Or Standard:**

N/a

1 type Shelf Life:

NSN 5305-00-401-5152

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0